

Screen Printing Inks

SCREEN ACTIVATOR 90.930 ECO

Code A31890930 ECO



PRODUCT DESCRIPTION

Spray solvent for opening of the meshes in the screen printing screens

APPLICATION FIELDS

This product is used in screen printing, during printing breaks, in order to avoid ink drying, by preventing obstruction of the meshes in the screen printing fabric.

APPLICATION PROCESS

| | |
|----------------------------|--|
| Substrates | Screen printing screens |
| Storage | Away from direct sunlight and heat sources |
| Package | Spray bomb |
| Security Data Sheet | Available upon request |

PREPARATION

SCREEN ACTIVATOR ECO is ready to use: after removing the ink from the matrix, spray it directly on both sides of the screen mesh.

TECHNICAL FEATURES

When the work begins again, make some sample prints, in order to rid the meshes of ink remnants. In that way, the screen will have open meshes, so it may be used in normal working conditions.

This product allows to avoid the mandatory washing of the printing screen, during the unavoidable work stoppages.

Thanks to its special formulation, this product is compatible with every ink.

SCREEN ACTIVATOR ECO allows to avoid the use of clothes soaked in solvent, in order to polish the obstructed matrix.

TECHNICAL FEATURES

- PAHs (Polycyclic aromatic hydrocarbons)-free
- Practical and easy to use
- Compatible with every solvent-based and UV-curing ink
- It avoids the use of clothes soaked in solvent, in order to polish the obstructed matrix

SPECIAL INSTRUCTIONS

- Always test the characteristics of the product, before starting production.
- The above information is the result of previous knowledge and experience; it is neither a guarantee nor an assurance.
- Direct the spray in concentric jets, for a short time.

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk.

While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product.

Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.